




## Husqvarna K 760 Cut-n-Break

*Husqvarna K 760 Cut-n-Break is a unique cutting method making it possible to cut as deep as 400 mm in stages with 230 mm twin blades. With a standard engine of 73 cc, the Cut-n-Break has taken a big step toward increased cutting capacity. Additionally, the power cutter features reduced noise levels and a high-efficiency vibration dampening system.*




### **MAKES 400 MM DEEP CUTS FROM ONE SIDE.**

Makes 400 mm deep cuts from one side.



### **LOW DIAMOND TOOL AND MAINTENANCE COST**

The Husqvarna K 760 Cut-n-Break is easy to use and maintain with very low diamond tool and maintenance cost.



### **NEW TYPE OF CUT-N-BREAK BLADE**

The power cutter now has a new type of Cut-n-Break blade, with an improved stable core and cutting performance.



### **SPECIALLY DEVELOPED PATENTED DIAMOND BLADES**

Twin, specially-developed 230 mm blades provide high cutting speed and power.

## Features Husqvarna K 760 Cut-n-Break

- Engine with X-Torq® produces 70 % less emissions, 20 % lower fuel consumption and more power.
- The new generation of Active Air Filtration™ is one of the most efficient air filtration systems on the market, delivering operational times (for dry cutting) of up to one year, with no filter service required.
- SmartCarb, a built-in automatic filter compensation, maintains high power and lowers fuel consumption.
- DuraStarter™, the dust-sealed starter, and the durable starter cord reduce the risk of downtime and increase reliability and product life.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To enable the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- EasyStart ensures 50% easier starting by reducing the compression in the cylinder during starting.
- All our cutters except the K 3000 Electric feature our robust new wet cutting kit, with low water usage.
- Sealed transmission reduces the wear and slippage risk.
- Fuel indicator on the tank shows fuel level, to help avoid unnecessary stoppages.
- DEX (Dust Extinguisher System)
- X-torq®
- Optimal ergonomics thanks to high power-to-weight ratio and low vibration levels.
- Optimised engine performance through efficient cylinder design, digital ignition system and X-Torq engine technology.
- Easy to start thanks to the digital ignition system, fast idle lock in choke lever and improved starter grip.
- The DEX system provides superior dust control and less water and slurry, with a new-designed water valve allowing for progressive water flow adjustment.
- Reliable operation and minimal service requirements through, Active Air Filtration™, new heat-resistant belt cover and DuraStarter™.
- SmartCarb™ and built-in automatic filter compensation maintains high power and lowers fuel consumption.

TECHNICAL SPECIFICATION	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	73.5 cm <sup>3</sup> / 4.48 cu.inch
Power output	3.7 kW
Fuel tank volume	0.9 lit / 30.4 fl oz
Idling speed	2700 rpm
Vibrations front handle	1.9 m/s <sup>2</sup>
Vibrations rear handle	2.8 m/s <sup>2</sup>
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	230 mm / 9 inch
Max cutting depth	400 mm / 16 inch
Weight (excl. cutting equipment)	9.6 kg / 21.2 lbs
Weight incl. cutting equipment	11.1 kg / 24.5 lbs
Fuel tank volume	0.9 lit / 1.9 US pint

