



Husqvarna Soff-Cut 150

The Husqvarna Soff-Cut 150 saw is designed for residential and light commercial applications. The lightest gas saw in the Soff-Cut range, the 150 is designed for ease of use and convenience. Features include a patented low noise blade enclosure which allows the unit to be used in residential areas with minimal disruption. In addition, the low-dust blade block system allows the saw to cut dry, and it controls the debris for easy cleanup.



SOFF-CUT™ TECHNOLOGY

Husqvarna Soff-Cut is a unique patented system for early entry concrete sawing. This technology enables concrete to be cut within the first one or two hours of finishing and before final set. Husqvarna Soff-Cut™ provides the best solution for minimizing the risk of random cracking, and it simplifies the working process, compared to conventional sawing.

Features Husqvarna Soff-Cut 150

- Patented low-noise and low-dust blade block enclosure.
- 4.3 hp engine with cyclone air filter.
- Mechanical blade depth control.
- Non-marking and non-stick polyurethane wheels.
- Retractable front guide system.
- Folding handle.
- Easy pull-start engine.
- Patented arbor.

TECHNICAL SPECIFICATION	
Motor manufacturer	Subaru
Motor spec	EX13
Max output (As rated by the engine manufacturer)	3.2kW / 4.3 hp
Engine/motor RPM	pos1:4000 rpm
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	7.69 cu.inch
Cylinder bore	2.28 inch
Cylinder stroke	1.89 inch
Fuel tank volume	0.7 gal.
Starter	Recoil
Engine cooling	Air
Number of belts	1
Displacement, l	126 lit
Oil capacity, l	0.6 lit
Output RPM	3800 rpm
Diamond blade, max	6 "
Max cutting depth	1.18 inch
Blade depth control	Manual
Blade control	Manual
Blade shaft diameter	0.75 inch
Blade flange	3 "
Blade shaft RPM	3800 rpm
Axle front	0.75 inch
Rear axle diameter	0.75 inch
Handle bars	Fixed
Primary wheel size	Outside diameter: 3 Wheel width: 3 Inner bore: 0 "
Secondary wheel size	Outside diameter: 3 Wheel width: 3 Inner bore: 0 "
Weight	87 lbs
Weight incl. packaging	91 lbs
Product size, LxWxH	68x19x33.5 inch
Sound power level, guaranteed (LWA)	99 dB(A)
Sound pressure	84 dB(A)
Hand arm vibration (Aeq)	7.9 m/s ²

